716M-NF



Coaxial Adapter 7-16 male - N female

Coaxial Adapter, 7-16 Male/N Female




Technical Features		
STRUCTURE		
Product Line		Coaxial Cable Components
Product Type		Coaxial Adapter
Coaxial Cable Type		Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable
MECHANICAL SPECIFICATIONS		
Connector A		7-16 DIN Male
Center Contact Connector A		Brass, silver plated
Outer Contact Connector A		Brass, silver plated
Connector B		N Female
Center Contact Connector B		Spring Bronze, silver plated
Outer Contact Connector B		Brass, silver plated
Body		copper alloy, nickel plated
Dielectric		PTFE
Gasket		Silicone rubber
Sealing class		IP68, connected
ELECTRICAL SPECIFICATIONS		
Frequency Range	MHz	DC - 8000
VSWR, Return Loss	VSWR (dB)	0-2000 MHz: 1.02 (40) 2000-2700 MHz: 1.04 (34) 2700-3700 MHz: 1.06 (30.5)
Insertion Loss (Max)	dB	0.02
3rd Order IM Product @ 2x20 Watts	dBc	< -165
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-45 to 85 (-49 to 185)
PACKAGING INFORMATION		
Package Quantity		1

716M-NF REV: C REV DATE: 07.DEC.2010 www.rfsworld.com



Coaxial Adapter 7-16 male - N female



External Document Links

Notes

716M-NF REV: C REV DATE: 07.DEC.2010 www.rfsworld.com