



221213-S

Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape

Dimensions

Nominal Size 1-1/4 in | 1-5/8 in | 1/2 in | 1/4 in | 2-1/4 in | 3/8 in | 5/8 in | 7/8 in

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	Four 1/2 in-7/8 in Twelve 1/2 in-1/2 in Twelve 1/2 in-7/8 in to device Two 1/2 in-2-1/4 in
Brand	ValuSite™
Includes	One roll of 2 in PVC tape One roll of 3/4 in PVC tape Six rolls of 2-1/2 in butyl rubber tape Two rolls of 3/4 in PVC tape
Material Type	Butyl rubber tape PVC tape
Ordering Note	CommScope® non-standard product
Package Quantity	1

Mechanical Specifications

UV Resistance Test Method	Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F PVC tape test method UL 510, ASTM D1000
UV Resistance, minimum with no degradation	=1000 hours
Weather Resistance Test Method	04AS00-03.6.0 MIL-STD-1344A, Method 1002

Packed Dimensions

Height	15.0 cm 5.9 in
Length	17.0 cm 6.7 in
Shipping Weight	1.52 kg 3.35 lb
Width	15.0 cm 5.9 in

Included Products

42615-10 — Butyl Rubber Tape, 24 in

9905-41 — Black 3/4 in PVC Tape, 66 ft